





[Home](#)Signed in as Triton | [sign out](#)RIBA  Insight

Triton Aqua Pump Pro - Basement Sumps

**Support information:**

-  **Frequently asked questions:** [How does NBS Plus work?](#) | [How do I comment on my NBS Plus product data?](#) | [What is NBS Create?](#)
-  **Quick links:** [Home](#) | [My products](#) | [How my products appear in NBS](#) | [How my products appear in NBS Create](#) | [Print this page](#)
-  **Resources:** [NBS Newsletter, Journal and eNewsletter](#) | [Terms and Conditions](#), [Disclaimer](#) and [Using the NBS Plus logo](#)
-  **Contact details:** [nbsplusproduction@thenbs.com](mailto:nbsplusproduction@thenbs.com) | T: 0845 456 9594

The information below is the NBS Plus product entry for Triton Systems Triton Aqua Pump Pro - Basement Sumps.

## Triton Aqua Pump Pro - Basement Sumps

A complete water control system specially designed for the removal of groundwater from basement cavity drainage membrane systems. The system comprises of a polyethylene sump, locking [access cover](#) (pedestrian duty, not suitable for roadways), a powerful submersible pump and a fittings kit. The system is very versatile, enabling the installer to locate inlets to their specifications.

**Features:**

- Pump capacity of 132 L/ min at 7 m head.
- Quick and easy to install.
- Standard 40 mm discharge pipes.

More about Triton Aqua Pump Pro - Basement Sumps:

[As standard](#)

**Triton Aqua Pump Pro - Basement Sumps**

- Manufacturer: Triton Systems.
  - Web: [www.tritonsystems.co.uk](http://www.tritonsystems.co.uk).
  - Tel: +44 (0)1322 318830.
  - Product reference: Triton Aqua Pump Pro.
- Accessories: [None].  
(AND) [\[1¼" brass gate valve\]](#).  
[\[12 V, 7 Ah Battery\]](#).  
[\[50 mm rubber seal \(inlet/ cable duct\)\]](#).  
[\[110 mm rubber seal \(drainage inlet\)\]](#).  
[\[Access cover, recessed 350 x 350 mm\]](#).  
[\[High level alarm \(mains operated\)\]](#).  
[\[High level alarm \(mains/ battery operated\)\]](#).

Add product

[top ^](#)

## Guidance for Triton Aqua Pump Pro - Basement Sumps from Triton Systems

More about Triton Aqua Pump Pro - Basement Sumps: [As standard](#)

**As standard****Pump:**


Mains powered, powerful 240 V submersible pump with float arm. It is capable of pumping up to 132 L/ min to a maximum head of 7 m.

**Sump basin:**

A red polyethylene pre-formed chamber, measuring 600 high with a diameter of 550 mm. It is most commonly located into the floor, finishing flush with the surrounding floor level. The sump basin is supplied with a locking, 350 x 350 mm access cover which can accept foot traffic. The lid can be easily removed to allow regular maintenance of the internal submersible pump or pumps.

**Non-return valve assembly:**


To avoid any discharged water backing-up into the sump basin, a non-return valve assembly is provided. This is fitted directly to the submersible pump outlet via flexible couplings and supplied ready to accept a standard 1¼" waste pipe.

**Further Information****Literature:**

[Triton Aqua Pro Sump Pump Install Guide](#)



[Triton Pumps and Drainage](#)

 Additional information may be available for [Triton Systems from ribaproductselector.com](http://Triton Systems from ribaproductselector.com).

**Contacts:**

[www.tritonsystems.co.uk](http://www.tritonsystems.co.uk)  
[technical@tritonsystems.co.uk](mailto:technical@tritonsystems.co.uk)  
T: +44 (0)1322 318830  
F: +44 (0)1322 524017

---

NBS Plus  
Triton, NBS Plus Approval Site, 24 September 2012  
[nbsplusproduction@thenbs.com](mailto:nbsplusproduction@thenbs.com) | T: 0845 456 9594