





[Home](#)Signed in as Triton | [sign out](#)RIBA  Insight

Triton Aqua Pump Pro Plus - Basement Sumps

**Support information:**

-  **Frequently asked questions:** [How does NBS Plus work?](#) | [How do I comment on my NBS Plus product data?](#) | [What is NBS Create?](#)
-  **Quick links:** [Home](#) | [My products](#) | [How my products appear in NBS](#) | [How my products appear in NBS Create](#) | [Print this page](#)
-  **Resources:** [NBS Newsletter, Journal and eNewsletter](#) | [Terms and Conditions](#), [Disclaimer](#) and [Using the NBS Plus logo](#)
-  **Contact details:** [nbsplusproduction@thenbs.com](mailto:nbsplusproduction@thenbs.com) | T: 0845 456 9594

The information below is the NBS Plus product entry for Triton Systems Triton Aqua Pump Pro Plus - Basement Sumps.

## Triton Aqua Pump Pro Plus - Basement Sumps

A complete water control system specially designed for the removal of groundwater from basement cavity drainage membrane systems. The system comprises of a polyethylene sump, locking [access cover](#) (pedestrian duty, not suitable for roadways), two powerful submersible pumps and a fittings kit. The system is very versatile, enabling the installer to locate inlets to their specifications.

It is identical to the Aqua Pump Pro system but is supplied with two mains powered pumps. These can be plumbed to either a single discharge outlet or to two separate outlets from the sump. The second mains pump is located on the raised foot within the chamber and provides back up to the primary pump and additional capacity to the system if required.

**Features:**

- Pump capacity of 132 L/ min at 7 m head (each).
- Quick and easy to [install](#).
- Standard 40 mm discharge pipes.

More about Triton Aqua Pump Pro Plus - Basement Sumps:

[As standard](#)

**Triton Aqua Pump Pro Plus - Basement Sumps**

- Manufacturer: Triton Systems.
  - Web: [www.tritonsystems.co.uk](http://www.tritonsystems.co.uk).
  - Tel: +44 (0)1322 318830.
  - Product reference: Triton Aqua Pump Pro Plus.
- Accessories: [None].
  - (AND) [\[1¼" brass gate valve\]](#).
  - [\[12 V, 7 Ah Battery\]](#).
  - [\[50 mm rubber seal \(inlet/ cable duct\)\]](#).
  - [\[110 mm rubber seal \(drainage inlet\)\]](#).
  - [\[Access cover, recessed 350 x 350 mm\]](#).
  - [\[High level alarm \(mains operated\)\]](#).
  - [\[High level alarm \(mains/ battery operated\)\]](#).

Add product

[top ^](#)

## Guidance for Triton Aqua Pump Pro Plus - Basement Sumps from Triton Systems

More about Triton Aqua Pump Pro Plus - Basement Sumps: [As standard](#)

**As standard****Pumps:**


Two mains powered, powerful 240 V submersible pumps with float arm. They are capable of pumping up to 132 L/ min to a maximum head of 7 m (each).

**Sump basin:**

A red polyethylene pre-formed chamber, measuring 600 high with a diameter of 550 mm. It is most commonly located into the floor, finishing flush with the surrounding floor level. The sump basin is supplied with a locking, 350 x 350 mm access cover which can accept foot traffic. The lid can be easily removed to allow regular maintenance of the internal submersible pump or pumps.

**Non-return valve assembly:**


To avoid any discharged water backing-up into the sump basin, a non-return valve assembly is provided. This is fitted directly to the submersible pump outlet via flexible couplings and supplied ready to accept a standard 1¼" waste pipe.

**Further Information****Literature:**

[Triton Aqua Pro Sump Pump Install Guide](#)



[Triton Pumps and Drainage](#)

 Additional information may be available for [Triton Systems from ribaproductselector.com](http://Triton_Systems_from_ribaproductselector.com).

**Contacts:**

[www.tritonsystems.co.uk](http://www.tritonsystems.co.uk)

[technical@tritonsystems.co.uk](mailto:technical@tritonsystems.co.uk)

T: +44 (0)1322 318830

F: +44 (0)1322 524017

---

NBS Plus

Triton, NBS Plus Approval Site, 24 September 2012

[nbsplusproduction@thenbs.com](mailto:nbsplusproduction@thenbs.com) | T: 0845 456 9594