



\*INSULATION SHOULD BE ABLE TO WITHSTAND POINT LOADING FROM MEMBRANE AND FLOOR BUILD UP

# TRITON

www.tritonsystems.co.uk

**Triton Systems**

Units 3 - 5 Crayford Commercial Centre  
Greyhound Way, Crayford, Kent. DA1 4HF

Telephone: **01322 318830**

Fax: **01322 524017**

Email: **info@tritonsystems.co.uk**

Web: **www.tritonsystems.co.uk**

THIS DRAWING IS THE PROPERTY OF TRITON SYSTEMS AND MUST NOT  
BE LOANED OR COPIED WITHOUT PRIOR WRITTEN CONSENT

© 2011 TRITON SYSTEMS

### NOTE

ALL INSTALLATION TO BE CARRIED OUT IN STRICT ACCORDANCE WITH  
MANUFACTURERS INSTALLATION INSTRUCTIONS. FOR FURTHER  
ASSISTANCE CONTACT TRITON TECHNICAL ON THE TELEPHONE  
NUMBER ABOVE.

REV.	MOD. BY	DATE	CHK. BY	APP. BY
<b>Alterations</b>				

### TITLE:

Typical Basement Perimeter  
Wall / Slab Junction

DRG. No.	TWS-064-1(D)	REV	3
----------	--------------	-----	---

DRAWN	JDF, CBS, TGL	System
DATE	25th October 2014	Files:
SCALE (A3)	Not To Scale	TWS-064-1(D).pdf
CHECKED		TWS-064-1(D).dwg
APPROVED		