

Triton Systems

Units 3-5 Crayford Commercial Centre, Greyhound Way

Crayford, Kent DA1 4HF

26/05/2015

Tel: 01322 318830 Fax: 01322 524017

info@tritonsystems.co.uk www.tritonsystems.co.uk

Revision Date

IRRITANT

MSDS Ref: **Publication Date** 04/04/1997 TR 300

1. PRODUCT NAME

TRIMOL RESINS 15,34,35,36,40,41

2. HAZARD IDENTIFICATION



Irritating to skin and eyes

3. COMPOSITION

HAZARDOUS INGREDIENT Bisphenol A and F epoxy Resins, diglycidyl ethers

CAS Nos. 25068-38-6, 68609-97-2 28064-14-4

Weight % 100

Symbols Xi (Irritant) Risk Phrases R36/38,43,51/53

4. FIRST AID

CONTACT WITH SKIN: Wash with plenty of soap and water.

CONTACT WITH EYES: Wash out with water for several minutes and seek medical advice.

INGESTION: Seek medical advice in the event of discomfort.

INHALATON: Remove to fresh air if fumes cause irritation of nose or throat.

OTHER INFORMATION: May aggravate existing respiratory problems.

5. FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Dry powder or foam. For small fires use CO2, never use water jet.

SPECIAL PROTECTIVE EQUIPMENT: For fires in confined spaces, use breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Wear suitable protective clothing appropriate to the amount involved,

which may include eye/face protection, PVC or synthetic rubber gloves,

protective footwear and overalls.

ENVIRONMENTAL PRECAUTIONS: Do not allow to enter public sewers and watercourses

If this cannot be avoided, inform the appropriate authority.

CLEAN-UP PROCEDURES: Absorb in dry sand or earth or similar absorbents and shovel into a

suitable closed container for disposal according to item 8.



7. HANDLING AND STORAGE

HANDLING PRECAUTIONS: Observe good hygiene standards and minimise skin contact.

Wear suitable protective clothing according to item 8.

STORAGE INFORMATION: Keep containers tightly closed in a cool place, out of direct sunlight.

Keep stored well ventilated.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION







Where prolonged or repeated exposure is likely, protective clothing should be worn, including eye protection, boots and PVC or synthetic rubber gloves.

Wash hands and exposed skin before meals and after work. Do not eat, drink or smoke whilst handling the product.

Do not wear contaminated clothing. Ventilate confined spaces thoroughly.

EXPOSURE LIMITS None prescribed in EH40

Slight irritant, not considered hazardous.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear, golden liquid
Odour	Faint
рН	7 (50% suspension in water)
Boiling Point	Decomposes
Melting Point	Not relevant
Flash Point	>150°C
Autoignition temperature	No data
Explosive properties	No data

Oxidising Properties	None
Vapour Pressure	1Pa (20°C)
Relative density	1.2-1.13 (15°C)
Bulk density	Not Relevant
Viscosity	No data
Solubility	Insoluble in water
Partition Coefficient	No data
Other data	

10. STABILITY / REACTIVITY

STABILITY: Stable under normal conditions of use.

CONDITIONS TO AVOID: High temperatures (degrades resin).

MATERIALS TO AVOID: Strong oxidising agents, acids and bases.

Excess of hardener (uncontrolled polymerisation reaction.

11. TOXICOLOGICAL INFORMATION

Not available data on acute toxicity. Irritating to eyes. A mild skin irritant and mild sensitising agent.



12. ECOLOGICAL INFORMATION

MOBILITY: Low soil absorption.

DEGRADABILITY: Not easily biodegradable.

ACCUMULATION: There is potential for bioaccumulation. Biomagnification is unlikely.

ECTOTOXICITY: Toxic to aquatic organisms: (TLm96: fish 1.2mg/litre, Daphnia

2.7mg/litre, algae 9.4mg/litre)

13. DISPOSAL INFORMATION

DISPOSAL OF PRODUCT: Chemical residues are normally regarded as special waste.

Dispose of in accordance with local and national regulations (incinerate

or landfill).

DISPOSAL OF PACKAGING: Uncleaned packaging should be treated as for the product.

14. TRANSPORT INFORMATION

UN No. None assigned PROPER SHIPPING NAME Liquid epoxy resin

ADR/RID Not classified as hazardous IMCO Not classified as hazardous

MFAG Table No. EmS No.

IATO/IACO Not classified as hazardous

PACKING GROUP

LABEL No hazard label

15. REGULATORY INFORMATION

CLASSIFICATION: Irritant

LABEL INFORMATION S24: Irritating to eyes and skin

S26: May cause sensitisation by skin contact.

S28: After contact with skin, wash immediately with plenty of water.

S37/39: Wear suitable gloves and eye/face protection.

Refer to other relevant legislation such as Health and Safety at Work etc., Act (HSWA), the Control of Substances Hazardous to Health Regulations (COSHH), the Environment Protection Act and the Control of Pollution Act.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risk as required by health and safety legislation.

16. OTHER INFORMATION

The information contained in this data is to the best of our knowledge accurate at the date of publication, but we cannot accept responsibility that it is sufficient or correct in all cases.

The data contained herein does not constitute a specification. Such information is available from the technical data sheet for the product.

Abbreviations: OES – occupational exposure standard. STEL – short-term exposure limit. LTEL – long term exposure limit. TWA – time weighted (8 hour) average. LEL – lower explosive limit. UEL – upper explosive limit.





Units 3-5 Crayford Commercial Centre, Greyhound Way

Crayford, Kent DA1 4HF

Tel: 01322 318830 Fax: 01322 524017

www.tritonsystems.co.uk

info@tritonsystems.co.uk

CORROSIVE

MSDS Ref: TR 301

Publication Date 04/04/1997

Revision Date 26/05/2015

1. PRODUCT NAME

TRIMOL HARDENER 15,34,35,36

2. HAZARD IDENTIFICATION



Corrosive - Causes burns Harmful if swallowed

May cause sensitisation by skin contact

Harmful to aquatic organisms, may cause long-term adverse effects in

the aquatic environment.

3. COMPOSITION

HAZARDOUS INGREDIENT Trimethlhexamethylene diamine CAS Nos. EC No. 25620-58-0 247-134-8 Weight % 100

Symbols C (Corrosive) Risk Phrases R22,34,43,52/53

4. FIRST AID

CONTACT WITH SKIN: Wash with plenty of soap and water. If irritation persists, obtain medical

CONTACT WITH EYES: Wash out with water for several minutes and seek medical advice.

INGESTION: Give plenty of water - if possible, charcoal slurry. Do not induce

vomiting.

INHALATON: Remove to fresh air. If symptoms persist, seek medical advice.

OTHER INFORMATION: Treat symptomatically.

5. FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Dry powder or foam. For small fires use CO2, never use water jet.

SPECIAL PROTECTIVE EQUIPMENT: For fires in confined spaces, use breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Wear suitable protective clothing appropriate to the amount involved,

which may include eye/face protection, PVC or synthetic rubber gloves,

protective footwear and overalls.

ENVIRONMENTAL PRECAUTIONS: Do not allow to enter public sewers and watercourses

If this cannot be avoided, inform the appropriate authority.

CLEAN-UP PROCEDURES: Absorb in dry sand or earth or similar absorbents and shovel into a

suitable closed container for disposal according to item 13.



7. HANDLING AND STORAGE

HANDLING PRECAUTIONS: Ensure adequate ventilation in work areas. Keep away from sources of

ignition - no smoking. Handle and open container with care.

STORAGE INFORMATION: Keep containers tightly closed in a cool place, out of direct sunlight.

Keep stored well ventilated. Keep away from food and feeding stuffs.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION







Wear protective clothing should be worn, including eye protection, boots and PVC or synthetic rubber gloves. In case of insufficient ventilation, wear suitable respiratory protective equipment.

Wash hands and exposed skin before meals and after work. Do not eat, drink or smoke whilst handling the product.

EXPOSURE LIMITS None prescribed in EH40

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear, colourless liquid
Odour	Amine - like
pH	11.3 (50% in water)
Boiling Point	>200°C
Melting Point	Not relevant
Flash Point	>180°C (CC)
Autoignition temperature	No data
Explosive properties	No data

Oxidising Properties	None
Vapour Pressure	6Pa (20°C)
Relative density	0.86-0.87 (20°C)
Bulk density	Not Relevant
Viscosity	5mPa.s (25°)
Solubility	Miscible in water
Partition Coefficient	No data
Other data	

10. STABILITY / REACTIVITY

STABILITY: Stable under normal conditions of use.

CONDITIONS TO AVOID: High temperatures, formation of aerosols, static discharges.

MATERIALS TO AVOID: Strong oxidising agents, acids and bases.

11. TOXICOLOGICAL INFORMATION

LD₅₀ (rat, oral): 910mg/kg. Eye irritation (rabbit): corrosive. Skin irritation (rabbit): Corrosive.

Dermal sensitisation (guinea pig): sensitiser.

12. ECOLOGICAL INFORMATION

MOBILITY: Avoid soil penetration.

DEGRADABILITY: Not easily biodegradable.

ACCUMULATION: There is potential for bioaccumulation. Biomagnification is unlikely.

ECTOTOXICITY: Toxic to aquatic organisms:

(LC₅₀ (fish) 96h:1000mg/litre, EC₅₀ (daphnia) 24h:31.5mg/litre EC₅₀ (algae) 72h: 29.5mg/litre), IC₅₀ (bacteria) 3h:100mg/litre).

13. DISPOSAL INFORMATION

DISPOSAL OF PRODUCT: Chemical residues are normally regarded as special waste.

Incinerate in compliance with the Environmental Protection Act 1990

(Process Guidance Note IPR5/1)

DISPOSAL OF PACKAGING: Uncleaned packaging should be treated as for the product. After

cleaning, can be landfilled.

14. TRANSPORT INFORMATION

UN No. 232

PROPER SHIPPING NAME Trimethylhexamethylene diamines, solution

ADR/RID Class 8. Item 53(c)

IMCO Class 8 IMDG Code page 08243

MFAG Table No. 320 EmS No. 8.05

IATO/IACO Class 8 PACKING GROUP 3

LABEL Corrosive



15. REGULATORY INFORMATION

CLASSIFICATION: Corrosive

LABEL INFORMATION R34: Causes burns

R22: Harmful if swallowed

R43: May cause sensitisation by skin contact

R52/53: Harmful to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

S26: In case of contact with eyes, rinse immediately with plenty of water

and seek medical advice.

S36/37/39: Wear suitable protective clothing, gloves and eye/face

protection.

S45: In case of accident or if you feel unwell, seek medical advice (show

the label where possible).

Refer to other relevant legislation such as Health and Safety at Work etc., Act (HSWA), the Control of Substances Hazardous to Health Regulations (COSHH), the Environment Protection Act and the Control of Pollution Act.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risk as required by health and safety legislation.



16. OTHER INFORMATION

The information contained in this data is to the best of our knowledge accurate at the date of publication, but we cannot accept responsibility that it is sufficient or correct in all cases.

The data contained herein does not constitute a specification. Such information is available from the technical data sheet for the product.

Abbreviations: OES – occupational exposure standard. STEL – short-term exposure limit. LTEL – long term exposure limit. TWA – time weighted (8 hour) average. LEL – lower explosive limit. UEL – upper explosive limit.





Units 3-5 Crayford Commercial Centre, Greyhound Way Crayford, Kent DA1 4HF

Tel: 01322 318830 Fax: 01322 524017

www.tritonsystems.co.uk

info@tritonsystems.co.uk

MSDS Ref: TR 308

Publication Date 15/04/1997

Revision Date 26/05/2015

HARMFUL

1. PRODUCT NAME

TRIMOL FILLERS 35 AND 36

2. HAZARD IDENTIFICATION



Contains respirable fraction silica – harmful by inhalation.

3. COMPOSITION

An inert, inorganic filler consisting of a mixture of silica sand and silica

flour.

4. FIRST AID

CONTACT WITH SKIN: Wash with plenty of soap and water.

CONTACT WITH EYES: Wash out with water for several minutes. Seek medical advice.

INGESTION: Not likely to cause any adverse affects in the amounts which could be

INHALATON: Remove to fresh air. Keep warm and at rest.

OTHER INFORMATION:

5. FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: As appropriate to surrounding fire.

SPECIAL PROTECTIVE EQUIPMENT: No particular requirements.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Wear respiratory protection if dust is generated.

ENVIRONMENTAL PRECAUTIONS: No environmental hazard.

CLEAN-UP PROCEDURES: Avoid dry sweeping and generation of dust. Damp down before

shovelling into a suitable container for disposal by landfill.



7. HANDLING AND STORAGE

HANDLING PRECAUTIONS: Keep and mix in original container. If necessary, wear suitable protective

clothing according to item 8.

STORAGE INFORMATION: No particular storage requirements. Keep dry to avoid deterioration.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION



Wear dust masks or the equivalent to BS2091 Type B, and provide dust extraction where dust is produced.

EXPOSURE LIMITS Refer to HSE Guidance Note EH40 for current critical silica

concentrations.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	White to buff-coloured powder/granules
Odour	None
pН	Not relevant
Boiling Point	Not relevant
Melting Point	>2000°C
Flash Point	Not combustible
Autoignition temperature	Not relevant
Explosive properties	Not explosive

Oxidising Properties	None
Vapour Pressure	Not relevant
Relative density	Not relevant
Bulk density	2700kg/m²
Viscosity	Not relevant
Solubility	Insoluble in water
Partition Coefficient	Not relevant
Other data	

10. STABILITY / REACTIVITY

STABILITY: Stable.

CONDITIONS TO AVOID: No special requirements.

MATERIALS TO AVOID: None.

11. TOXICOLOGICAL INFORMATION

Inert, insoluble and non-toxic. The main health hazard is inhalation of the respirable fraction silica.

12. ECOLOGICAL INFORMATION

MOBILITY: Not mobile in soil.

DEGRADABILITY: Inert and not biodegradable.

ACCUMULATION: There is no likelihood of bioaccumulation or biomagnification.

ECTOTOXICITY: Not ecotoxic.



13. DISPOSAL INFORMATION

DISPOSAL OF PRODUCT: Dispose of by landfill in a commercial site, in accordance with local and

national regulations.

DISPOSAL OF PACKAGING: As for the product.

14. TRANSPORT INFORMATION

Not regulated by road, rail, sea or air.

15. REGULATORY INFORMATION

CLASSIFICATION: Not classified as hazardous.

LABEL INFORMATION None.

Refer to other relevant legislation such as Health and Safety at Work etc., Act (HSWA), the Control of Substances Hazardous to Health Regulations (COSHH), the Environment Protection Act and the Control of Pollution Act.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risk as required by health and safety legislation.

16. OTHER INFORMATION

The information contained in this data is to the best of our knowledge accurate at the date of publication, but we cannot accept responsibility that it is sufficient or correct in all cases.

The data contained herein does not constitute a specification. Such information is available from the technical data sheet for the product.

Abbreviations: OES – occupational exposure standard. STEL – short-term exposure limit. LTEL – long term exposure limit. TWA – time weighted (8 hour) average. LEL – lower explosive limit. UEL – upper explosive limit.