

PLATON CAVITY MEMBRANES (TYPE) CAN BE INCORPORATED FOR COMBINED PROTECTION SEE TWS-047-1 (C) FOR A RETROFIT DETAIL



Triton Systems

Units 3-5 Crayford Commercial Centre, Greyound Way, Crayford, Kent, DA1 4HF

Telephone: 01322 318830 Fax 01322 524017

Email: info@tritonsystems.co.uk Web: www.tritonsystems.co.uk

THIS DRAWING IS THE PROPERTY OF TRITON SYSTEMS AND MUST NOT BE LOANED OR COPIED WITHOUT PRIOR WRITTEN CONSENT

© 2018 TRITON SYSTEMS

NOTE

ALL INSTALLATION TO BE CARRIED OUT IN STRICT ACCORDANCE WITH MANUFACTURERS INSTALLATION INSTRUCTIONS. FOR FURTHER ASSISTANCE CONTACT TRITON TECHNICAL ON THE TELEPHONE NUMBER ABOVE.

THIS TRITON TYPICAL DETAIL IS INTENDED FOR GUIDANCE ONLY AND IS NOT A DESIGN. THE CONCRETE THICKNESSES AS ILLUSTRATED RELATE TO THE REQUIREMENT FOR IT ADMIX PERFORMANCE AND ARE NOT INTENDED TO IMPLY SUITABILITY FOR ANY SPECIFIC STRUCTURAL REQUIREMENTS FOR A PROJECT.

REV MOD. BY CHECK. BY DATE

TITLE

SERVICE ENTRY SEALING USING TT WATERSTOP

TYPE B INTEGRAL WATERPROOFING TT ADMIX

DRAWN	MB, MD	DRAWING NO:
DATE	APR 2018	TTA - 015
SCALE	N.T.S	117